



Hot Applied Joint Sealants

Specification	Right/Pointe *	Crafco	Deery/CMC	W.R. Meadows	P&T Products
ASTM D 5078 (Crumb Rubber)	5078	34232 34240	CMC 180 CMC 280 NR-100 NR-200 CMC 5078	CR-90	Dura-Fill 5078
ASTM D 6690 Type I (ASTM D 1190) AASHTO M 324 (AASHTO M 173) FED SS-S-164	1190	34203 34211	CMC 103 100% Poly CMC 103 Regular CMC 103 G.L.	164 1190	Dura-Fill 1190
ASTM D 6690 Type II (ASTM D 3405) AASHTO M 324 (AASHTO M 301) FED SS-S-164	3405 3405 Rubber 3405 Parking Lot 3405 All Virgin	34201 34220 34221 34534	CMC 102P CMC 102 Regular CMC 102 G.L.	Hi-Spec 3405	Dura-Fill 3405
ASTM D 6690 Type IV (ASTM D 3405 Modified) Various state D.O.T.	3405 Modified	34231	CMC 101	Sof-seal 3405M	3405 LM
Direct Fire	Direct Fire	34532	Super Stretch Stretch Pro-PL Stretch 229	Parking Lot Sealant	Dura-Fill HS
Polymer & Fiber	Poly Fiber – Easy Flow	Poly-Fiber	CMC AC-20 & Fiber	N/A	N/A

* Note: Only Right/Pointe sealants have the Fast Set Additive

888-755-5700

www.rightpointe.com